



KONVEKTA

Technical leadership starts with ideas.

Operating instructions for KONVEKTA air conditioning units **StreamLine** SL700–SL800–SL850–SL900



with control KS600-CAN

R134a

24 Volt DC

ID#: BBA-KL7S012AB
Version: A02

Konvekta AG

Am Nordbahnhof 5
34613 Schwalmstadt
Germany



+49 (0) 66 91 / 76 – 0



+49 (0) 66 91 / 76 - 200



Info@konvekta.com

www.konvekta.com

Contents

Page:

• Introduction	3
• Information on the operating instructions	4
1. Technical data	5
1.1. Compressor type K VX	5
2. Intended Use	5
2.1. Generally information for a/c unit	6
2.2. Operating Conditions	6
3. Operation	6
3.1. Operation panel / function of the keys	7
3.2. Special functions of the KS600	10
4. Maintenance / Service	11
4.1. Troubleshooting	11
5. Warranty Conditions	12
6. Waste disposal in accordance with legal provisions	12
7. History of modification	12

Appendix:

- Maintenance Schedule [WP07050618](#)

Introduction

These operating instructions have been written for drivers, operators and the maintenance staff of your air conditioning unit.

In this context, we refer implicitly to the compliance with our general installation guidelines. These can be obtained from the KONVEKTA technical after sales service: TKD@konvekta.com.

Please observe our valid safety instructions, available under www.konvekta.de/asv.html. In case of order placement or any other conclusion of contract the safety instructions get integral part of the contract.

These operating instructions have to be read carefully and made use of before the first start-up and after that regularly by each person who is involved in handling the machine:

- Operation including troubleshooting and waste disposal of fuels and auxiliary agents.
- Servicing, inspection, repair
- Transport

This facilitates the handling and avoids trouble caused by improper operation. Working in compliance with these operating instructions increases operation reliability and service life of the air conditioning unit and reduces life cycle costs.

Please complete these instructions by adding the national provisions for prevention of accidents and environmental protection.

These instructions are part of the air conditioning unit. Always have a copy at hand in the driver's cabin.

You will certainly understand that we will not recognize any warranty claims due to improper handling, inadequate maintenance, applications that do not correspond with the determined use, utilization of non-admitted fuels or the non-observance of safety provisions.

KONVEKTA will annul without notice all obligations concerning guarantee, service contracts etc. regardless if granted by KONVEKTA or its distributors in case other than original KONVEKTA spare parts or parts bought from KONVEKTA AG have been used for maintenance and repair. These operating instructions contain all necessary information to operate your air conditioning unit. In case you need more explanations please contact the next KONVEKTA service station.

^① On our website www.konvekta.com in category >service< you will find a survey of contact details of all our service partners close to your location.

Information on the operating instructions

These operating instructions are valid for the air conditioners - and heating systems type:

➤ SL700	➤ SL800
➤ SL850	➤ SL900

with control KS600-CAN

☞ When taking the unit into operation we recommend adding the following data. This will also be important for your orders of spare parts, and in case of warranty.

Serial number of the unit:

Order No.:

Year of construction:/ (MM/JJ)

Date of first operation://..... (TT/MM/JJ)

The machine is in accordance with the EC machinery directive 2006/42/EC.

The unit contains or needs fluorinated greenhouse gas for operation and is subject to identification requirements in accordance with F-Gas Regulation 517/2014.

Due to the fact that scope of supply depends on the order, equipment of your product may differ in some parts of description.

In case your product is equipped with details not shown or described in the operating instruction, your KONVEKTA -Service-Station will always be at disposal for informing you about correct operation.

In the course of further developments we reserve the right to technical modifications without notice. Guarantee and liability conditions of KONVEKTA AG's general business conditions are not enlarged by the above notes.

Indications and photos should neither be copied and circulated nor used for competitor's purposes. All rights according to the copyright remain expressly reserved.

Manufacturer: KONVEKTA AG, Postfach 2280, D-34607 Schwalmstadt

1. Technical data

Type	SL700	SL800	SL850	SL900
Cooling capacity [Watt]	35.000	39.000	41.000	44.000
Cooling capacity [kcal/h]	30.100	33.600	35.300	37.900
Cooling capacity [BTU/h]	119.600	133.200	140.100	150.300
Heating capacity Q100 [Watt]	44.000	44.000	47.000	47.000
Air capacity free blowing [m/h ³]	7080	7080	9440	9440
Max. current consumption at 26V [A]	77	77	92	107
Current consumption At normal operation 26V [A]	20	20	24	28
Compressor	KVX40/560K	KVX40/655K	KVX40/655K	KVX50/755K
Measurements L/B/H [mm]	4050/1890/210			
Refrigerant	R134a			
GWP	1.430			
Limitation of operation [°C]	>50			
Roof radius [m]	>8			



Important!

In vehicles that are equipped with an a/c unit with heating function the heating medium has to consist of water/glycol – antifreeze protection (conform the mixing ratio to manufacturers` instructions). This is absolutely necessary to prevent the heaters from frost damage!
 (The prevalent antifreeze filling of the vehicle manufacturers goes down to -40°C.)

1.1. Compressor type KVX

Carry out the first oil change with the first maintenance, then every 3 years. Also clean the oil intake strainer. The oil charge is dependent on the compressor type (see table).

Compressor type	KVX40/560K	KVX40/655K	KVX50/755K
Weight	34 kg	35 kg	43 kg
Refrigerant oil / Quantity (Liter)	Esteröl SE55 / 2	Esteröl SE55 / 2	Esteröl SE55 / 2,5
Magnetic clutch	24V DC	24V DC	24V DC



Important:

To avoid leakages at the shaft seal of the compressor:

The compressor should be started every 4 weeks for approx. 15 minutes!

This also applies when the vehicle is not into operation for a longer period or when the air conditioning unit is not used!

2. Intended Use

The **KONVEKTA** air conditioner represents an air conditioning system that works with the ozone friendly refrigerant R 134a and which creates a pleasant and individually adjustable room temperature by means of forced convection. The determined use includes also the observance of the Operating instruction and the proof of regular inspections as well.

2.1. Generally information for a/c unit



Attention in case of roof top a/c units: Never switch on the a/c unit during car-wash!

- The a/c unit is operational with running engine only.
- At cooling operation the humidity inside the vehicle is decreased, which avoids steamed up windows.
- The a/c unit works most effectively with windows and doors shut. If, however, the interior of the standing vehicle has been heated up severely by exposure to sunlight, short-time opening of windows and doors may accelerate the cooling down process.
- At high outside temperature and humidity condensate might drip off the evaporator and make a puddle under the vehicle. This is quite normal and no sign for a leakage.
- The filter in the return air grid (optional) retains pollution. If the external air is contaminated with gas switch over to return air operation. The filter should be cleaned or replaced respectively on a regular basis so that the capacity of the a/c unit is not affected.
- If you think that the air conditioning unit has been damaged **switch it off immediately** in order to avoid further damage. The air conditioning unit may be taken into operation again only after it has been checked at a KONVEKTA Service Station.

① On our website www.konvekta.com in category >service< you will find a survey of contact details of all our service partners close to your location.

2.2. Operating Conditions

NOTE: KONVEKTA uses components made of copper and aluminium, which last a whole unit lifetime under normal environmental conditions. Should the units be operated under aggressive environmental conditions, i.e. air containing salt-, phosphate- or ammoniac extremely, a corrosion of the copper- and aluminium components cannot be ruled out. The copper- and aluminium components of the KONVEKTA systems are not suitable for such extreme application conditions. We indicate emphatically, that corrosion is not subject to warranties for defects. KONVEKTA does not take over any warranties for defect, neither for corrosion nor for consequential damage resulting there from, nor for damages caused by cleaning the systems with highly compressed or corrosion advancing substances.

3. Operation



Attention in case of roof top a/c units: Never switch on the a/c unit during car-wash!

Danger of accidents!

- Focussing your attention on the road traffic is of top priority.
- Only operate your air conditioning unit when the traffic situation allows it!
- Please note that the control panel keys have not been designed for heavy stressing.
- Excessive or fast pressing of the keys for adjusting the set temperature does not accelerate the cooling down process. It possibly damages the control panel and so affects the general performance of the air conditioning unit.

3.1. Operation panel / function of the keys



Rotary knob K1



Rotary knob	Functional description
Turn	When the ignition is ON, the air distribution flap can be adjusted by turning the knob. Rights DEFROST setting for the window only when alternator ON

Rotary knob K2



Rotary knob	Functional description
Turn	When the ignition is ON, the fan speed can be adjusted from the driver's place. When alternator is OFF only min. speed.

Rotary knob K3



Rotary knob	Functional description
Turn	When the ignition is ON, the desired cockpit channel temperature can be adjusted. (12 - 90 °C) Left stopper is OFF.

Key S1



Keypress	Functional description
Short press	Switching on the driver's area air conditioning. Its only active when the passenger compartment air conditioner is ON
Long press	---
Double-click	---
Key combination	---

Key S2



Keypress	Functional description
Short press	Turns the driver's seat to recirculation.
Long press	---
Double-click	---
Key combination	---

Key S3



Keypress	Functional description
Short press	Turns ECO (AUTO without compressor) ON and OFF.
Long press	---
Double-click	---
Key combination	---

Key S4



Keypress	Functional description
Short press	Turns Automatic ON and OFF.
Long press	Can be switched between AUTO / HEAT / COOL.
Double-click	---
Key combination	 +  You get into the service modus. Ignition OFF:  +  Querying the error message.  +  System time set.

Key S5



Keypress	Functional description
Short press	Switches the air conditioning for example for 20min at REHEAT.
Long press	---
Double-click	---
Key combination	---

Key S6



Keypress	Functional description
Short press	Switches the air conditioning for 10min. to recirculation.
Long press	---
Double-click	---
Key combination	---

Key S7



Keypress	Functional description
Short press	Reducing the manual fan settings in 7 steps.
Long press	---
Double-click	---
Key combination	---

Key S8



Keypress	Functional description
Short press	Reducing the room set temperature for the passenger compartment. After reaching the minimum Temperature 6 x press key >> MAX COOL.
Long press	---
Double-click	---
Key combination	---

The temperature is set between 12 ° and 28 °. The main display of the display is the room set temperature.

Key S9



Keypress	Functional description
Short press	Switches the auxiliary heater ON.
Long press	---
Double-click	---
Key combination	Ignition OFF :  +  Preheater start time set.

Key S10



Keypress	Functional description
Short press	Increasing the manual fan settings in 7 steps.
Long press	---
Double-click	---
Key combination	 +  You get into the service modus. Ignition OFF:  +  Querying the error message.

With the button the fan is manually adjusted in 7 steps. Manual setting has precedence over AUTO.

Key S11



Keypress	Functional description
Short press	Increasing the room set temperature for the passenger compartment. After reaching the maximum Temperature 6 x press key >> MAX HEAT.
Long press	---
Double-click	---
Key combination	Ignition OFF :  +  System time set.  +  Preheater start time set.

The desired temperature is set between 12 ° and 28 °. The main display of the display is the desired room temperature.

3.2. Special functions of the KS600

With these buttons, special functions are activated:

Activate SMOG:

2 x  Switch from the cockpit and cabin air recirculation flap for example 10min to recirculation. = SMOG

Switch over Function MODE:

2 x  Switch from Function Mode = AUTO - HEAT - COOL - AUTO button on the double.

Function Mode	System heating	System ventilation	System cooling
AUTO	X	X	X
HEAT	X	X	--
COOL	--	X	X

Switch Display:

2 x  Switch the display of clock - room temperature - Outdoor temperature time.

Check air duct temperature:

5sec +  Switch from the display for 5 seconds on channel temperature.

Check FB temperature:

 +  Switch from the display for 5 seconds on driver temperature.

Enable keyboard lock:

10sec.  +  Key lock is enabled, the display stands and "Loc". Manual fan cabin and set temperature setting is disabled.

Check hours of operation

 +  When ignition is OFF by pressing the keys the operating hour counters are called.

1 = operating hours unit

2 = operating hours compressor

Note: h = hours, d = days, Y= year

4. Maintenance / Service

Please arrange regular dates for maintenance works and services with a KONVEKTA service station, as indicated in maintenance schedule bus no.: [WP07050618](#). On our website www.konvekta.com in category >service< you will find a survey of contact details of all our service partners close to your location.

- Only qualified staff is allowed to carry out these works! -

For general instructions on repair – and maintenance works please contact via email:

TKD@konvekta.com



Danger of accidents!

Qualified staff in charge of installation and maintenance have to be trained in accordance with EN 378-Part 4 and (EC) No.307/2008 and must strictly follow the legal provisions.

Any works or modifications at the air conditioner which are carried out improperly can lead to malfunction and so endanger operational reliability. We recommend having all works and modifications carried out at an authorized KONVEKTA Service Station.

Before carrying out any maintenance works at your air conditioning unit, carefully read the KONVEKTA safety provisions (TD00052A) in order to avoid any dangers and accidents!

4.1. Troubleshooting



Only qualified staff is allowed to carry out these works!

Trouble	Cause	Repair <i>By authorized Service Station only</i>
a/c is not running	thermostat open	– check inside temperature ^① – re-adjust thermostat ^①
	electric connection disconnected	– check electric connections at switchboard
	relay defective	– check relay, replace if necessary
	defrost thermostat has switched off	– check evaporator blower, replace if necessary
	outside temperature too low (possible icing of evaporator)	– switch on „ventilation“ only
	evaporator coil dirty	– clean evaporator coil with compressed air
	magnetic clutch	– check connections at magnetic clutch
	compressor does not compress	– check high and low pressure, replace compressor if necessary
	excess pressure (pressure too high)	– check axial fans – check fuses at switchboard – clean condenser coil with compressed air
	excess pressure caused by high outside temperature	– run unit until pressure has stabilized ^①
	leakage in a/c unit, lack of refrigerant	– check a/c unit for leakages – refill refrigerant
Loud noise at compressor	low pressure, screen of expansion valve clogged	– clean screen; replace dryer
	defective bearing at compressor	– replace either bearing or entire compressor
	slack V-belt	– check V-belt at compressor drive

^① By operator

5. Warranty Conditions

The current „General Warranty Conditions“ KONVEKTA AG“ will apply. A copy will be furnished by the warranty department. Please contact gwl@konvekta.com.

6. Waste disposal in accordance with legal provisions

After the phase of use the last proprietor is responsible for the adequate waste management. The environmental regulations in the exporting country must be observed.

The following list contains the most important regulating literature, valid for the *Federal Rep. of Germany*:

- Resolution for dangerous substances
- Law for waste circulation (KRW/AfgG))
- Resolution for the proofs of utilization and removal
- Criminal Code (StGB) 28th section „criminal acts against the environment“ §326 - Environment jeopardizing waste management
- Law of chemicals § 27 - penal prescriptions
- Resolution for used oil
- Law of water balance
- Resolution for the waste management of old cars and the adaptation of road prescriptions
- Resolution (EC) No. 2037/2000 of the European Parliament and of the Council for materials that affect the ozone layer
- Resolution to prohibit certain ozone destroying halogen hydrocarbons.

The used refrigerant endangers the environment. When dealing with refrigerants the existing prescriptions and regulations are to be followed. **Only qualified staff is allowed to carry out these works!**

Water endangering substances - acc. to §§19g-19l - are solid, liquid, and gaseous substances. e.g.: mineral and tar oils (cooling oils), halogen containing organic combinations (refrigerants).

© Source of supply:
- Bundesanzeiger
- Beuth Verlag
- dtv (Deutscher Taschenbuch Verlag)

7. History of modification

Version	Date	Name	Remark	File
A00	13.02.2014	B. Keßler	Source file	BAKL8S012AA
A01	01.03.2016	B. Keßler	Resolution (EC) No.2037/2000 was (EWC) No. 3093/94; pressure switches deleted	BAKL8S012AA
A02	02.03.2017	B. Keßler	Information on the operating instructions and technical data expanded with F-gas-regulation	BAKL8S012AA